

LF570 / LF550

HIGH PERFORMANCE RIDE-ON REEL MOWER



- **PERFECT COMBINATION OF CUT QUALITY AND PERFORMANCE**
- **OUTSTANDING CONTOUR FOLLOWING**
- **TRUSTWORTHY KUBOTA ENGINE**

Mow with ease with the LF range of larger area, lightweight reel mowers. This high-performance ride-on mower range will give you a consistent cut on the fairway or the sports fields.

Outstanding speed and cutting controls combine with power and Jake's signature cut trusted by generations, to give you superb agility and the ultimate finish. The mowers also have outstanding fuel capacity, allowing you to work for longer, with a lighter touch.

CUT
WIDTH
100"
(2.54M)

ERGONOMICS
PROGRAMMABLE
**SPEED
CONTROL**

CUTTING
CAPACITY
UP TO 8 AC
(3.24HA) / HR
AT 8MPH (12.9KM/H)

CUTTING
REELS
**5" (12.7CM) OR
7" (17.78CM)**

MOWER
ENGINE
KUBOTA®
37.5/50.2HP
(28/37.4KW) DIESEL

TRANSPORT
SPEED
12MPH
(19.3KPH)



SINCERELY

Jake

For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946



Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.

© 2023 Textron Specialized Vehicles Inc.

LF570 / LF550

HIGH PERFORMANCE RIDE-ON REEL MOWER



REELS AND BLADES

NUMBER AND SIZE	9 or 11 heavy section fairway blades
BLADE MATERIAL	Hardened, high manganese carbon steel
CUTTING UNIT LIFT	Hand operated, joystick controlled hydraulic lift system, one-touch lift/lower control for all reels

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Variable displacement, electronically controlled hydrostatic drive; 4WD models: SureTrac™ parallel-cross-series traction system, four high-torque wheel motors, 2WD in reverse.
REEL DRIVE	Fixed displacement hydraulic motors with FlashAttach quick disconnect coupled reel motors. Standard on-board backlapping.
HYDRAULIC SYSTEM	14 gal. (53L) capacity; hydraulic tank oil level monitor and horn alarm; GreensCare biodegradable fluid; full-flow, 10-micron filter. Side-by-side radiator/hydraulic oil cooler.
SERVICE BRAKES	Dynamic braking through traction system
PARKING BRAKES	Semi-automatic, wet parking brakes integrated in front wheel motors
STEERING	Rear wheel, hydrostatic power steering with tilt adjustable steering wheel
MOWING SPEED	Selectable up to 11mph (19km/h)
REVERSE SPEED	Selectable up to 5mph (8km/h)

WEIGHTS & DIMENSIONS

	2WD	4WD
WEIGHT (excluding fuel)	2wd 3221lbs (1461kg) 2wd 37.5HP (28kW) 3467lbs (1573kg)	4wd 3552lbs (1611kg) 4wd 50.2HP (37.43kW) 3798lbs (1723kg)
LENGTH (less catchers)	108" (2.74m)	
OVERALL HEIGHT (ROPS up)	88" (2.23m)	
WHEELBASE	58" (1.5m)	
TRANSPORT WIDTH	87" (2.2m)	
WORKING WIDTH	115" (2.92m)	

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

- 55.9cm (22") Front rollers ranging from 5.1cm (2") to 7.6cm (3") - solid tube steel, grooved assembled or machined aluminum or steel
- Turf Groomer®
- Powered rear roller cleaning brush
- Canopy/Sunshade
- Grass Catcher
- High-cut kit
- Premium air suspension seat
- LED operator platform light kit
- Hood locking latch (required for CE)
- Verticut reels